

Concrete

12x24 Porcelain



03WBC011224




03WBC041224



03WBC051224



03WBC061224



2x2 Mosaic



QuickSHIP (noted colors only)

Tile: 12x24

Special Order

Tile: 12x24

Mosaic: 2x2

Trim: 4x24 Bullnose

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	> 400 lbf
Bond Strength	ASTM C482	> 200 psi
Facial Dimension	ASTM C499	± 0.15%
Range of Thickness	ASTM C499	0.025"
Warpage	ASTM C485	± 0.20%
Wedging	ASTM C502	± 0.30%
Chemical Resistance	ASTM C650	Unaffected
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.50%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	0.42-0.52

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11-13/16" x 23-13/16"	8.5mm	Unpolished	-
2" x 2" Mosaic	11-3/4" x 11-3/4" -OR- 11-15/16" x 11-15/16" sheet *	8.5mm	Unpolished	-
4" x 24" Bullnose	3-13/16" x 23-13/16"	8.5mm	Unpolished	-

* Depending on color. See QR code for details.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

