

# Main Street

**Crossville, Inc.** PO Box 1168  
Crossville, TN  
38557

**Phone** 931.484.2110  
**Fax** 931.456.2956  
**E-Mail** [Crossc@CrossvilleInc.com](mailto:Crossc@CrossvilleInc.com)  
**Web** [CrossvilleInc.com](http://CrossvilleInc.com)

## Recommended Use

Main Street is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Main Street is not recommended for exterior horizontal surfaces or exterior paving. If offset pattern is required for tiles 18 inches or longer, Crossville® recommends an offset of not greater than 33%. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage. See [CrossvilleInc.com](http://CrossvilleInc.com) for detailed installation instructions.

## Wet area use for Main Street mosaics

Crossville® produces the Main Street mosaics with the Cross-Sheen® (UPS) finish. The AcuTest™ Wet Dynamic COF of the Main Street UPS finish is  $\geq .58$ . Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Main Street to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

## Care and Maintenance

Regular cleaning is the best way to keep Main Street tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at [CrossvilleInc.com](http://CrossvilleInc.com).

## EcoCycle Tile Process™

Main Street contains a minimum of 4 percent pre-consumer recycled content and is manufactured by Crossville® using processes that recycle nearly 12 million pounds of previously discarded filtrate and fired tile waste. In addition to its own fired waste recycling, Crossville also accepts and recycles reclaimed, previously installed tile through its Tile Take-Back™ Program. For more information, visit [CrossvilleInc.com](http://CrossvilleInc.com)/green.

## Green Squared™ Certified

Crossville® has earned Green Squared™ certification from the Tile Council of North America (TCNA) for its entire U.S.-manufactured porcelain product line-up, as well as its manufacturing processes. The company is among the first ever recipients of this certification standard for the tile industry. TCNA developed the Green Squared certification under American National Standards Institute (ANSI) process. The multi-attribute program (ANSI A138.1) scores products in five categories of performance: product characteristics, manufacturing, corporate governance, innovation and end-of-life. Crossville's certified products and processes received stringent evaluation from Scientific Certification Systems (SCS), the green building industry's longest standing third-party certifier.

## Hydrotect

Our porcelain tiles are available with Hydrotect™. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. For complete details check our website at [CrossvilleInc.com](http://CrossvilleInc.com).



## National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

## Exterior Cladding

Crossville's Porcelain Stone® Exterior Cladding Systems are suitable for virtually any conventional masonry application. When used in conjunction with our exterior cladding systems, Crossville's Porcelain Stone offers clear advantages: decreased construction costs, less site disturbance, low-to-zero maintenance after installation, accelerated construction schedules and greater strength than traditional masonry.

## Crossville® Sample Express

### Sample fulfillment & Help Line

[Samples@CrossvilleInc.com](mailto:Samples@CrossvilleInc.com)  
1 800 221.9093

### Loose Samples for Architects & Designers

### Loose Tile Samples

Sizes may vary depending on product series  
Max. of 4 large field tile per order

### Replacement Chips for PSS Rack

Max. of 5, 2 x 2 chips per color

### Standard Shipping

UPS Ground

## Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at [CrossvilleInc.com](http://CrossvilleInc.com).

*Information listed here is subject to change.*

*Please refer to [CrossvilleInc.com](http://CrossvilleInc.com) for the latest, most accurate information.*

## Trade Organizations



## Environmentally Aware

