

Portugal

Crossville, Inc.

PO Box 1168
Crossville, TN
38557

Phone 931.484.2110
Fax 931.456.2956
E-Mail Crossc@CrossvilleInc.com
Web CrossvilleInc.com

Recommended Use

Portugal UPS is recommended for interior floors, walls, counter tops and exterior walls in both residential and commercial applications. Portugal EXT is recommended for exterior floors and walls in both residential and commercial applications. **If offset pattern is required for tiles 15 inches or longer, Crossville® recommends an offset of not greater than 33%.** See CrossvilleInc.com for detailed installation instructions.

Wet area use for Portugal Mosaics

Crossville® produces the Portugal 2 x 2 and Crossville mosaics with the Cross-Sheen® (UPS) finish. The AcuTestSM wet Dynamic COF of Portugal is ≥ 0.42 . Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Portugal to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

Environmentally Conscious

Portugal is Made in the U.S.A. through Crossville's EcoCycle Tile Process, Portugal is Green Square Certified and contains a minimum 4% pre-consumer recycled content. Portugal is covered by Crossville's porcelain tile EPD, HPD, Declare Label, and sustainability report—all of which can contribute to LEED, Well, LBC, and other green building rating systems. Portugal is a beautifully responsible selection for your commercial and residential design projects. Crossville also accepts and recycles reclaimed, previously installed tile through its Tile Take-Back™ Program. For more information, visit CrossvilleInc.com/green.

Care and Maintenance

Regular cleaning is the best way to keep Portugal tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville products is available at CrossvilleInc.com.

Our Warranty

Crossville Inc guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Hydrotect

Our porcelain tiles are available with Hydrotect. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. Please request a sample before ordering. For complete details check our website at CrossvilleInc.com.



Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

Crossville's Porcelain Stone® Exterior Cladding Systems are suitable for virtually any conventional masonry application. When used in conjunction with our exterior cladding systems, Crossville's Porcelain Stone offers clear advantages: decreased construction costs, less site disturbance, low-to-zero maintenance after installation, accelerated construction schedules and greater strength than traditional masonry.

Complimentary Samples are available at CrossvilleInc.com/products/Portugal/

Samples may also be ordered through customer service by email or phone.

Sample Fulfillment & Help Line

Samples@CrossvilleInc.com
1 800 221.9093

Loose Tile Samples for Architects & Designers

Loose Tile Samples

Sizes may vary depending on product series
Max. of 4 large field tile per order

Replacement Chips for PSS Rack

Max. of 5, 2 x 2 chips per color

Standard Shipping

UPS Ground

Trade Organizations



Environmentally Aware

