

# Notorious

12x24 Porcelain



03NTR011224H (honed)  
03NTR011224U (unpolished)



03NTR021224H (honed)  
03NTR021224U (unpolished)



03NTR051224H (honed)  
03NTR051224U (unpolished)



12x12 Mosaic



03NTR031224H (honed)  
03NTR031224U (unpolished)



03NTR041224H (honed)  
03NTR041224U (unpolished)



03NTR061224H (honed)  
03NTR061224U (unpolished)



Tile: 3x15 - 12x12 - 12x24 - 24x24  
24x36

Mosaic: 12x12

Trim: 4x12 Bullnose - 6x12 Cove Base

For more information  
and images:



## Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	> 500 lbf
Bond Strength	ASTM C482	> 200 psi
Chemical Resistance	ASTM C650	<b>Unaffected</b>
Frost Resistance	ASTM C1026	<b>Resistant</b>
Water Absorption	ASTM C373	< 0.20%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	<b>0.42-0.52 (Honed); 0.50-0.60 (Unpolished)</b>

Nominal Size	Actual Size	Thickness	Finish	Rectified
3" x 15"	2.83" x 14.65"	10.5 mm	Honed or Unpolished	Yes
12" x 12"	11.69" x 11.69"	10.5 mm	Honed or Unpolished	Yes
12" x 24"	11.69" x 23.5"	10.5 mm	Honed or Unpolished	Yes
24" x 24"	23.5" x 23.5"	10.5 mm	Honed or Unpolished	Yes
24" x 36"	23.5" x 35.3"	10.5 mm	Honed or Unpolished	Yes
12" x 12" Mosaic	12" x 12"	10.5 mm	Unpolished	-
4" x 12" Bullnose	3.82" x 11.69"	10.5 mm	Honed or Unpolished	-
6" x 12" Cove Base	5.91" x 11.69"	10 mm	Unpolished	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

