

Portugal

12x24 Porcelain



03PTG011224UPS



03PTG021224UPS



03PTG041224UPS



2x2 Mosaic



Triangle Mosaic



03PTG031224UPS



03PTG051224UPS



03PTG061224UPS



- Tile: 6x24 - 12x24 - 24x24 - 24x48
- Mosaics: 2x2 - Triangle
- Trim: 4x24 Bullnose - 6x12 Cove Base
- Outdoor: 12x24 - 24x24

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	> 500 lbf
Bond Strength	ASTM C482	> 200 psi
Chemical Resistance	ASTM C650	Unaffected
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.20%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	0.50-0.60 (Unpolished); 0.60-0.70 (Exterior)

Nominal Size	Actual Size	Thickness	Finish	Rectified
6" x 24"	5.79" x 23.5"	10.5 mm	Unpolished	Yes
12" x 24"	11.69" x 23.5"	10.5 mm	Unpolished or Exterior	Yes
24" x 24"	23.5" x 23.5"	10.5 mm	Unpolished or Exterior	Yes
24" x 48"	23.5" x 47.13"	10.5 mm	Unpolished	Yes
2" x 2" Mosaic	11.73" x 11.73"	10.5 mm	Unpolished	-
Triangle Mosaic *	8.54" x 14.65"	10.5 mm	Unpolished	-
4" x 24" Bullnose	3.78" x 23.5"	10.5 mm	Unpolished	-
6" x 12" Cove Base	5.91" x 11.69"	10 mm	Unpolished	-

* Due to this mosaic's design, caution should be used when installing on surfaces that might contact bare skin or other delicate materials. To prevent possible injury or damage from sharp corners that might be exposed above the grout line, install per ANSI 108 guidelines in order to minimize or prevent lippage.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

