


Retro Active 2.0

12x24 Porcelain



03RET051224PTN (ptn)
03RET051224PO (pol)
03RET051224UPS (ups)



03RET091224PTN (ptn)
03RET091224PO (pol)
03RET091224UPS (ups)



03RET081224PTN (ptn)
03RET081224PO (pol)
03RET081224UPS (ups)



03RET071224PTN (ptn)
03RET071224PO (pol)
03RET071224UPS (ups)



03RET041224PTN (ptn)
03RET041224PO (pol)
03RET041224UPS (ups)



03RET031224PTN (ptn)
03RET031224PO (pol)
03RET031224UPS (ups)



03RET021224PTN (ptn)
03RET021224PO (pol)
03RET021224UPS (ups)



03RET011224PTN (ptn)
03RET011224PO (pol)
03RET011224UPS (ups)



03RET111224PTN (ptn)
03RET111224PO (pol)
03RET111224UPS (ups)



03RET121224PTN (ptn)
03RET121224PO (pol)
03RET121224UPS (ups)




03RET061224PTN (ptn)
03RET061224PO (pol)
03RET061224UPS (ups)



03RET101224PTN (ptn)
03RET101224PO (pol)
03RET101224UPS (ups)



03RET131224PTN (ptn)
03RET131224PO (pol)
03RET131224UPS (ups)



Pattern



2x4 Mosaic



- Tile: 3x12 - 4x12 - 4x24 - 6x12
6x24 - 12x12 - 12x24
- Mosaic: 2x4
- Trim: 4x12 Bullnose - 6x12 Cove Base
2x12 Cove Base - 1x6 Corner
2x2 Corner - 2x4 Corner

For more information
and images:



Retro Active 2.0

Porcelain



Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	> 350 lbf
Bond Strength	ASTM C482	> 200 psi
Chemical Resistance	ASTM C650	Class A (Pattern, Unpolished); Class B (Polished)
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.20%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	0.42-0.52 (Pattern); 0.31-0.41 (Polished); 0.50-0.60 (Unpolished)

Nominal Size	Actual Size	Thickness	Finish	Rectified
3" x 12" *	2-3/4" x 11-3/4"	5/16"	Pattern, Polished or Unpolished	-
4" x 12" *	3-3/4" x 11-3/4"	5/16"	Pattern, Polished or Unpolished	-
4" x 24" *	3-3/4" x 23-3/4"	5/16"	Pattern, Polished or Unpolished	-
6" x 12" *	5-3/4" x 11-3/4"	5/16"	Pattern, Polished or Unpolished	-
6" x 24" *	5-3/4" x 23-3/4"	5/16"	Pattern, Polished or Unpolished	-
12" x 12"	11-3/4" x 11-3/4"	5/16"	Pattern, Polished or Unpolished	-
12" x 24"	11-3/4" x 23-3/4"	5/16"	Pattern, Polished or Unpolished	-
2" x 4" Mosaic	11-3/4" x 11-3/4"	5/16"	Unpolished	-
4" x 12" Bullnose	3-3/4" x 11-3/4"	5/16"	Pattern, Polished or Unpolished	-
6" x 12" Cove Base	5-7/8" x 11-3/4"	3/8"	Unpolished	-
2" x 12" Cove Base	1-3/4" x 11-11/16"	3/8"	Unpolished	-
1" x 6" Inside or Outside Corner	1" x 5-7/8"	-	Unpolished	-
2" x 2" Inside Corner	1-3/4" x 1-3/4"	-	Unpolished	-
2" x 4" Outside Corner	1-3/4" x 3-1/2"	-	Unpolished	-

* Noted sizes are custom cut – Inquire with a sales representative for lead time. Edges on these tiles are beveled.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possiblelippage from one tile to the next.