

Entice

8x48 Color Body Porcelain

mosaic 
Products. Design. Solutions.



15ENTPAL848N (natural look)



15ENTPAL760E (elegant look)



15ENTCOP848N (natural look)



15ENTCOP760E (elegant look)



15ENTASH848N (natural look)



15ENTASH760E (elegant look)



15ENTBRO848N (natural look)



15ENTBRO760E (elegant look)

The “Natural” version and Grip and Outdoor Pavers feature an innovative Sensitech finish that combines superior slip resistance with a soft touch, ensuring easy cleaning and maintenance.



Special Order (Import 10-12 Weeks)

Tile: 7x60 Elegant or Natural -
8x48 Natural

Mosaic: N/A

Trim: 3x48 - 3x60 Natural Bullnose

Outdoor: 9mm 8x48 Natural Grip -
20mm 12x48 Natural Paver

Not all colors available in all sizes or finishes

For more information
and images:



Made in Italy
v.6-24

Technical Characteristics

Specs	Test Method	Requirements for Nominal Size			Test Result			
		7 cm ≤ N < 15 cm (mm)	N ≥ 15 cm (%)		(mm)	Matte Sensitech	Matte	Grip 9mm
Length and Width	10545-2	± 0.9 Non-Rect. ± 0.4 Rect.	± 0.6 Non-Rect. ± 0.3 Rect.	± 2.0 Non-Rect. ± 1.0 Rect.	Pass			
Thickness		± 0.5	± 0.5	± 0.5	Pass			
Straightness of Sides		± 0.8 Non-Rect. ± 0.4 Rect.	± 0.5 Non-Rect. ± 0.3 Rect.	± 1.5 Non-Rect. ± 0.8 Rect.	Pass			
Water Absorption	10545-3	≤ 0.5% Individual Maximum 0.6%			≤ 0.1%			
	ASTM C373	≤ 0.5%			≤ 0.5%			
Breaking Strength	ISO 10545-4	S ≥ 700N (for thickness < 7.5 mm) S ≥ 1300N (for thickness ≥ 7.5 mm)			S ≥ 1500 N			
Modulus of Rupture		R ≥ 35 N/mm ²			R ≥ 40 N/MM ²			
Bending Strength	EN 1339 Annex F	-			-			≥ U3 30x120
Impact Resistance	10545-5	Declared Value			≥ 0.55			
MOHs Hardness	EN 101	-			6			
Abrasion Resistance	10545-6	≤ 175 mm ³			≤ 150 MM ³			
Thermal Shock Resistance	10545-9	Pass			Pass			
Frost Resistance	10545-12	Pass			Pass			
Stain Resistance	10545-14	Declared Class			5			
Bond Strength	EN 1348	Declared Value			≥ 1.0 N/mm ² (Class C2 - EN 12004)			
Reaction to Fire	-	Class A1 or A1 _{fl}			A1 or A1 _{fl}			
Chemical Resistance - Household and Pool Salts	10545-13	Minimum Class B			A			
Chemical Resistance - Acids and Alkalis Low Concentrate		Declared Class			LA			
Chemical Resistance - Acids and Alkalis High Concentrate		Declared Class			HA			
DCOF	ANSI A 326.3	-			≥ 0.50	≥ 0.42	≥ 0.55	

Nominal Size	Actual Size	Thickness	Finish	Rectified
7" x 60"	7.28" x 59.05"	9 mm	Matte	Yes
8" x 48"	7.87" x 47.24"	9 mm	Matte	Yes
8" x 48" Grip	7.87" x 47.24"	9 mm	Matte	Yes
12" x 48" Paver	11.81" x 47.24"	20 mm	Matte	Yes
3 x 48 Bullnose	7.2" x 47.24"	-	Matte	-
3 x 60 Bullnose	7.2" x 59.05"	-	Matte	-

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

Installation Note: Due to its linear plank shape, this material requires particular care when it comes to installation. The tile will look its best when offset is less than 33%. The staggered installation will minimize lippage which is common in tiles of this format. No claim will be honored after installation.