

Alstein

12x24 Porcelain



74ALSIVO1224



74ALSLIG1224



74ALSGRA1224



74ALSIVO2M



74ALSLIG2M



74ALSGRA2M



QuickSHIP

Tile: 12x24

Mosaic: 2x2

Trim: N/A

Recommended Jolly Edge Trim: 3/8"

ALSIVO - A100 Ivory

ALSLIG - J100 Gray

ALSGRA - J100 Classic Gray

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result
Warpage Diagonal	ASTM C485	670.6 mm ±0.5%
Warpage Edge	ASTM C485	599.8 mm ±0.5%
Water Absorption	ASTM C373	≤ 0.5
Breaking Strength	ASTM C648	≥ 275 lbf
Visible Abrasion Resistance	ASTM C1027	PEI IV
Thermal Shock Resistance	ASTM C484	Resistant
Crazing Resistance	ASTM C424	Resistant
Frost Resistance	ASTM C1026	Resistant
Dynamic Coefficient of Friction	ANSI A137-1	≥ 0.42
Chemical Resistance	ASTM C650	Class A Resistant
Stain Resistance	ASTM C1378	Class A

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.81" x 23.62"	8.5 mm	Matte	-
2" x 2" Mosaic	11.75" x 11.75"	8.5 mm	Matte	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.



For your convenience, select products are stocked in our Central Service Center.