

Sediment

12x24 Porcelain



75SEDWHI1224 (matte)
75SEDWHI1224P (polished)



75SEDTAU1224 (matte)
75SEDTAU1224P (polished)



75SEDWHI2PPM



75SEDTAU2PPM



QuickSHIP

Tile: 12x24 Matte

Mosaic: 2x2

Trim: 3x24 Bullnose

Non-QuickSHIP items are available for commercial projects only. Inquire with a sales representative for additional information.

Tile: 12x24 Polished

For more information and images:



Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	≥ 325 lbs.
Scratch Hardness	MOH'S	7 (Matte); 4-5 (Polished)
Chemical Resistance	ASTM C650-04	Class IV (Matte); A (Pol.)
Abrasion Resistance	ASTM C1027	Class III
Thermal Shock Resistance	ASTM C484	Resistant
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.5%
DCOF (Wet)	ASTM C1028	≥ 0.42 (Matte)
Category of Use	ANSI A326.3	IW (Matte); ID (Polished)

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11-3/4" x 23-11/16"	8.2 mm	Matte	-
12" x 24"	11-3/4" x 23-9/16"	9.0 mm	Polished	Yes
2" x 2" Mosaic	11-3/4" x 11-3/4"	8.2 mm	Matte	-

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.



For your convenience, select products are stocked in our Central Service Center.