



Taj Opus

12x24 Porcelain



75TAJPAL1224 (matte) 
75TAJPAL1224P (polished)




75TAJMIR1224 (matte) 
75TAJMIR1224P (polished)



1x3 Herringbone
Mosaic 



75TAJEMP1224 (matte) 
75TAJEMP1224P (polished)



4" Hexagon Mosaic



2x2 Mosaic 



QuickSHIP (MOSAICS COMING SOON)

Tile: 12x24

Mosaic: 2x2 - 1x3 Herringbone

Special Order

Tile: 24x24 - 24x48

Mosaics: 4" Hexagon

Trim: 4x24 Bullnose

For more information
and images:





Technical Characteristics

Test Item	Test Method	Test Result	
		Matte	Polished
Breaking Strength	ASTM C648	≥ 425 lbs.	
Scratch Hardness	MOH'S	4-5	7
Chemical Resistance	ASTM C650-04	Class E	
Abrasion Resistance	ASTM C1027	Class III	Class IV
Thermal Shock Resistance	ASTM C484	Resistant	
Frost Resistance	ASTM C1026	Resistant	
Water Absorption	ASTM C373	≤ 0.5%	
DCOF (Wet)	ASTM C1028	N/A	≥ 0.42
Category of Use	ANSI A326.3	ID	IW

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.75" x 23.56"	9.0 mm	Matte or Polished	Yes
24" x 24"	23.56" x 23.56"	9.0 mm	Matte or Polished	Yes
24" x 48"	23.56" x 47.31"	9.0 mm	Matte or Polished	Yes
1" x 3" Herringbone Mosaic	11.75" x 11.75"	9.0 mm	Matte	-
2" x 2" Mosaic	11.75" x 11.75"	9.0 mm	Matte	-
4" Hexgaon Mosaic	11.75" x 11.75"	9.0 mm	Matte	-
4" x 24" Bullnose	4" x 23.56"	9.0 mm	Matte	-

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.



For your convenience, select products are stocked in our Central Service Center.