

# Stream

12x24 Glazed Porcelain

mosaic   
Products. Design. Solutions.



78STRBON1224



78STRSIL1224



2x2 Mosaic



Hexagon Mosaic



**QuickSHIP (48 Hours)**

Tile: 4x12 - 12x24

Mosaics: 2x2 - 12x12 Hexagon

Trim: 3x12 Bullnose

For more information  
and images:



### Technical Characteristics

Test Item	Test Method	Test Result
Water Absorption	ISO 10545-3	< 0.5%
Breaking Strength	ISO 10545-4	≥ 43 N/mm <sup>2</sup>
Surface Abrasion Resistance	ISO 10545-7	PEI 5
Thermal Shock Resistance	ISO 10545-9	Guaranteed
Frost Resistance	ISO 10545-12	Guaranteed
Chemical Resistance	ISO 10545-13	GA (V); GLA (V); GHA (V)
Stain Resistance	ISO 10545-14	Compliant
Dynamic Coefficient of Friction	DCOF	> 0.42
Slip Resistance	DIN 51130	R9

Nominal Size	Actual Size	Thickness	Rectified
4" x 12"	3.94" x 11.81"	9 mm	-
12" x 24"	11.81" x 23.62"	9 mm	Yes
2" x 2" Mosaic	11.81" x 11.81"	9 mm	-
Hexagon Mosaic	12.2" x 13.78"	9 mm	-
3" x 12" Bullnose	2.76" x 11.81"	9 mm	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.



For your convenience, select products are stocked in our Central Service Center (available within 48 hours).