

Astoria

12x24 Porcelain



88ASTGRA1224



88ASTGRA2M



QuickSHIP

Tile: 12x24 (40 faces)

Mosaic: 2x2

Trim: N/A

Recommended Edge Trim:
3/8" A100 Aluminum Jolly

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result
Water Absorption	ASTM C373	≤ 0.5
Breaking Strength	ASTM C648	≥ 250 lbf
Visible Abrasion Resistance	ASTM C1027	PEI IV
Thermal Shock Resistance	ASTM C484	Resistant
Crazing Resistance	ASTM C424	Resistant
Frost Resistance	ASTM C1026	Resistant
Dynamic Coefficient of Friction	ANSI A137-1	≥ 0.42
Chemical Resistance	ASTM C650	Class A Resistant
Stain Resistance	ASTM C1378	Class A

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.8" x 23.62"	8.5 mm	Matte	-
2" x 2" Mosaic	11.75" x 11.75"	8.5 mm	Matte	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.



For your convenience, select products are stocked in our Central Service Center.