

Calacatta Oro

12x24 Porcelain



88CALORO1224 (matte)



88CALORO1224P (polished)



Tile: 12x24 - 24x48

Mosaic: N/A

Trim: N/A

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result	
		Matte	Polished
Water Absorption	ASTM C373	≤ 0.5%	
Breaking Strength	ASTM C648	Min. 335	
Scratch Hardness	MOH'S	5	3
Chemical Resistance	ASTM C650	Unaffected	
Frost Resistance	ASTM C1026	Resistant	
PEI - Glazed Tiles	ASTM C1027	4	3
Minimum Bond Strength (PSI)	ASTM C482	165	
Dynamic Coefficient of Friction (DCOF)	ASTM C1028	≥ 0.42	≤ 0.40
Facial Dimensions	ASTM C499	Pass	
Range of Thickness	ASTM C499	Pass	
Warpage	ASTM C485	Pass	
Wedging	ASTM C502	Pass	
Recycled Content	--	28/%	

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.81" x 23.62"	9 mm	Matte or Polished	Yes
24" x 48"	23.62" x 47.24"	9 mm	Matte or Polished	Yes

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

