



# Nordico

12x24 Porcelain



13x13 Mosaic



88NORSNO1224 (matte)  
88NORSNO1224P (polished)



### QuickSHIP

Tile: 12x24

### Special Order

Tile: 24x24 - 35x35

Mosaic: 13x13

Trim: 3x12 Bullnose

*Not all colors available in all sizes or finishes*

For more information  
and images:



### Technical Characteristics

Test Item	Test Method	Test Result
Water Absorption	ASTM C373	≤ 0.5%
Breaking Strength	ASTM C648	Min. 335
Scratch Hardness	MOH'S	5 (Matte); 3 (Pol.)
Chemical Resistance	ASTM C650	Unaffected
Frost Resistance	ASTM C1026	Resistant
Minimum Bond Strength (PSI)	ASTM C482	165
Dynamic Coefficient of Friction (DCOF)	ASTM C1028	≤ 0.40 (Matte); ≤ 0.33 (Pol.)
Facial Dimensions	ASTM C499	Pass
Range of Thickness	ASTM C499	Pass
Warpage	ASTM C485	Pass
Wedging	ASTM C502	Pass

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.81" x 23.62"	8.5 mm	Matte or Polished	Yes
24" x 24"	23.62" x 23.62"	9 mm	Matte or Polished	Yes
35" x 35"	35.43" x 35.43"	10 mm	Polished	Yes
13" x 13" Mosaic	12.98" x 12.98"	8.5 mm	Matte	-
3" x 12" Bullnose	2.98" x 12.2"	8.5 mm	Matte	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.



For your convenience, select products are stocked in our Central Service Center.