

Serena

12x24 Glazed Porcelain

mosaic 
Products. Design. Solutions.



88SERBON1224C (crosscut)



88SERBON1224V (veincut)



88SERMOK1224C (crosscut)



88SERMOK1224V (veincut)



Tile: 12x24 - 24x48 - 48x48 - 48x110

Mosaic: N/A

Trim: N/A

Outdoor: 20mm 24x36 (Crosscut only)

Not all colors available in all sizes or finishes

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result
Water Absorption	ASTM C373	$\leq 0.5\%$
Breaking Strength	ASTM C648	≥ 350
Scratch Hardness	MOH'S	6
Chemical Resistance	ASTM C650	Unaffected
Frost Resistance	ASTM C1026	Resistant
PEI - Glazed Tiles	ASTM C1027	III
Minimum Bond Strength (PSI)	ASTM C482	165
Dynamic Coefficient of Friction (DCOF)	ASTM C1028	≥ 0.42
Facial Dimensions	ASTM C499	Pass
Range of Thickness	ASTM C499	Pass
Warpage	ASTM C485	Pass
Wedging	ASTM C502	Pass
Recycled Content	--	28/%

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.81" x 23.62"	9 mm	Matte	Yes
24" x 36" Paver	23.62" x 35.72"	20 mm	Matte	Yes
24" x 48"	23.62" x 47.24"	9 mm	Matte	Yes
48" x 48"	47.24" x 47.24"	9 mm	Matte	Yes
48" x 110"	47.24" x 110.23"	6 mm	Matte	Yes

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.