

Statuary

12x24 Porcelain



88STABLA1224P (polished)



88STAWHI1224U (matte)



88STAWHI13H (matte)



2x2 Mosaic (matte)



QuickSHIP (noted colors only)

Tile: 6x24 - 12x24

Mosaics: 1x3 Herringbone - 2x2

Trim: 3x24 Bullnose

Special Order

Tile: 13x13 - 24x24 - 24x48 - 35x35

Wall Tile: 3x6 - 3x6 Beveled - 4x10 -

4x10 Beveled - 6x18

Trim: 3x13 Bullnose - 3x6 Wall Bullnose -


3x9.5 Wall Bullnose - 3x10 Wall

Bullnose - 6x18 Wall Bullnose

Not all colors available in all sizes or finishes

For more information
and images:





Technical Characteristics

Test Item	Test Method	Test Result - Porcelain	Test Result - Hex	Test Result - Wall
Water Absorption	ASTM C373	≤ 0.5%	< 3%	> 10%
Breaking Strength	ASTM C648	Min. 335	Min. 335	Meets or Exceeds
Scratch Hardness	MOH'S	3 (Pol); 5 (UPS)	5	N/A
Chemical Resistance	ASTM C650	Unaffected	Unaffected	Unaffected
Frost Resistance	ASTM C1026	Resistant	Resistant	N/A
Minimum Bond Strength (PSI)	ASTM C482	165	165	N/A
Dynamic Coefficient of Friction (DCOF)	ASTM C1028	< 0.40 (Pol); ≥ 0.42 (UPS)	≥ 0.42 (UPS)	N/A
Facial Dimensions	ASTM C499	Pass	Pass	N/A
Range of Thickness	ASTM C499	Pass	Pass	N/A
Warpage	ASTM C485	Pass	Pass	Pass
Wedging	ASTM C502	Pass	Pass	Pass
Recycled Content	--	5% Pre-Consumer	17% Pre-Consumer	25% Pre-Consumer

Nominal Size	Actual Size	Thickness	Finish	Rectified
6" x 24"	5.67" x 23.62"	8.5 mm	Matte	-
12" x 24"	11.81" x 23.62"	8.5 mm	Matte or Polished	Yes
13" x 13"	12.99" x 12.99"	8.5 mm	Matte	-
24" x 24"	23.62" x 23.62"	9 mm	Matte or Polished	Yes
24" x 48"	23.62" x 47.24"	10 mm	Matte or Polished	Yes
35" x 35"	35.43" x 35.43"	10 mm	Matte or Polished	Yes
1" x 3" Herringbone Mosaic	12.16" x 11.57"	8.5 mm	Matte	-
2" x 2" Mosaic	11.75" x 11.75"	8.5 mm	Matte	-
3" x 6" Wall	2.95" x 5.91"	7 mm	Bright or Matte	-
4" x 10" Wall	4.33" x 9.84"	7.3 mm	Bright or Matte	-
6" x 18" Wall	5.91" x 17.72"	8 mm	Bright	-

Trim: See QR code for additional details on available options.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.



For your convenience, select products are stocked in our Central Service Center.